bonga®
SIDEWALLS

GENERAL:

Fabric material	• Single coated 740 g/m² or double coated 560 g/m²
Fabric characteristics	• Fire retardant M2 / B1 • Water column 10 000 mm (single coated) - 8000 mm (double coated) • Tensile strength 1200 N / 5 cm (single coated) - 1000 N / 5 cm (double coated) • Watertight PVC coating on the outside (single coated) or on the inside and outside (double coated) • UV-index: 8 • Zippers and buckles to roll side walls up
Wooden poles	• Pinewood • Sleeves to slide side keder into • Pole cap to protect the canvas • Steel bases with holes for anchoring with pegs and/or screws • Eye bolts at the top of the poles for anchoring with straps • Height: 2.75 m • Diameter: 7 cm
Aluminium profile	• Anodised aluminium • Sleeves to slide top keder into
Panoramic window	• Transparent 625 g/m² PVC • Fire retardant M2 • Optimal UV-protection

BASE

3 x 2.75 m



Panoramic window

3 x 2.75 m

Closed

2 x 2.75 m



Panoramic window

2 x 2.75 m

Closed

EXTENSION

3 x 2.75 m

Panoramic window

3 x 2.75 m

Closed

2 x 2.75 m

Panoramic window

2 x 2.75 m

Closed

AVAILABLE COLOURS

Double coated

Single coated